

Specifications

Luzon S2 R32

- Wi-Fi Control with Samsung SmartThings and Bixby voice controls.
- Twin Rotary Compressor with Digital Inverter Boost technology.
- Triple Protector Plus to protect compressor, fan and controller from power surges.
- Direct drive fan powered by a BLDC motor.
- Compatible with wired remote controller and with centralized controller.
- AI Auto Comfort



			Indoor Unit	AR50F09C1BHNEU	AR50F12C1BHNEU	AR50F18C1BHNEU	AR50F24C1BHNEU
			Outdoor Unit	AR50F09C1BHXEU	AR50F12C1BHXEU	AR50F18C1BHXEU	AR50F24C1BHXEU
Capacity							
Capacity	Cooling (Nominal)	kW		2,5	3,5	5	6,5
	Cooling (Min–Max)	kW		0.9 - 3.35	0.9 - 3.8	1.6 - 6.7	1.4 - 7.6
	Heating @ +7 °C	kW		3.2	3.5	6	7.4
	Heating (Min–Max)	kW		0.9 - 4.3	0.9 - 4.7	1.3 - 8	1.2 - 9.7
	Heating @ -5 °C	kW		2.8	2.87	5.27	6.55
	Heating @ -10 °C	kW		2.68	2.72	4.86	5.92
	Heating @ -15 °C	kW		2.37	2.33	4.1	5.09
Performance							
Energy Efficiency Cooling	SEER ¹	W/W		6.7/ A++	6.6/ A++	7/ A++	6.8/ A++
	Power Consumption	kWh/a		130.60	185.61	334.56	250.00
	Pdesignc	kW		2,5	3,5	5	6,5
	EER	W/W		3,29	2,6	3,6	3,33
Energy Efficiency Heating	SCOP ¹	W/W		4.0/ A+	4.0/ A+	4.1/ A+	4.3/ A+
	Power Consumption	kWh/a		735.00	805.00	1334.88	1297.56
	Pdesignh (average)	kW		2.1	2.2	3.8	4.1
	COP ¹	W/W		3,64	3,61	3,73	3,36
Moisture Removal		l/h		1.0	1.5	2	2.5
Maximum Airflow (Cooling)	Indoor Unit	m ³ /min		10.5	10.9	15.7	17.7
	Outdoor Unit	m ³ /min		38	38	50	50
Sound Power	Indoor Unit (Cooling)	dB(A)		54	56	58	62
	Outdoor Unit (Cooling)	dB(A)		63	63	65	68
Sound Pressure	Indoor Unit High/Silent Mode	dB(A)		38 / 16	40 / 16	41 / 25	45 / 27
	Outdoor Unit High	dB(A)		45	46	51	54
Operating Temperature Range	Cooling	°C		-10-46	-10-46	-10-46	-10-46
	Heating	°C		-15-24	-15-24	-15-24	-15-24
Electrical Data							
Power Source		Φ, V, Hz		1Φ, 220-240 V, 50 Hz	1Φ, 220-240 V, 50 Hz	1Φ, 220-240 V, 50 Hz	1Φ, 220-240 V, 50 Hz
Compressor Type	Outdoor Unit	Type		Twin Rotary	Twin Rotary	Twin Rotary	Twin Rotary
Power Consumption	Cooling	W		760	1345	1390	1950
	Heating	W		880	970	1610	220
Operating Current	Cooling	A		3.4	6	6.4	8.8
	Heating	A		4	4.4	7.8	9.8
Dimensions							
Net Dimensions (W x H x D)	Indoor Unit	mm		820 x 299 x 215	820 x 299 x 215	1,055 x 299 x 215	1,055 x 299 x 215
	Outdoor Unit	mm		710 x 540 x 220	710 x 540 x 220	880 x 638 x 310	880 x 638 x 310
Net Weight	Indoor Unit	kg		9,1	9,1	12,5	12,5
	Outdoor Unit	kg		24,8	24,8	40,1	42

¹ Energy labels as shown are according to EU No 626/2011 (LOT 10) label classification 2019, on a scale from D to A+++.

² The centralized controller is only compatible with specific bigger capacity ODU i.e. AR18TXHZAWKXEU and AR24TXHZAWKXEU. It is not compatible with the 2.5kW and 3.5kW RAC ODU. A MIM-R10N Interface is required for the Outdoor Unit (ODU).



Indoor Unit	AR50F09C1BHNEU	AR50F12C1BHNEU	AR50F18C1BHNEU	AR50F24C1BHNEU
Outdoor Unit	AR50F09C1BHXEU	AR50F12C1BHXEU	AR50F18C1BHXEU	AR50F24C1BHXEU

Refrigerant			R32 (contains fluorinated greenhouse gases. GWP = 675)			
Refrigerant	Type		R32 (contains fluorinated greenhouse gases. GWP = 675)			
	Charging (for 5 m)	kg	0.53	0.53	1.3	1.3
	Charging Ton Equivalent CO ₂	tCO ₂ e	0.36	0.36	0.88	0.88
	Additional Refrigerant Charging	g/m	15	15	15	15
Piping Connections	Liquid Pipe	ø, mm (inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Pipe	ø, mm (inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2)	15.88 (5/8)
Piping Length	Min/Max (ODU to IDU)	m	3/15	3/15	3/30	3/30
Piping Height	Max	m	8	8	15	15
Piping Connections	Drain Pipe	ø, mm	ø16.3, 550 mm	ø16.3, 550 mm	ø16.3, 550 mm	ø16.3, 550 mm
Functions						
Airflow	WindFree™ Cooling					
	Air Direction Control (Up/Down)		Auto	Auto	Auto	Auto
	Air Direction Control (Left/Right)		Auto	Auto	Auto	Auto
	Auto Fan Speed		●	●	●	●
Air Purification	Tri-Care Filter		-	-	-	-
	Easy Filter Plus		●	●	●	●
	Auto Clean (Self-Cleaning)		●	●	●	●
Operating Mode	AI Auto Comfort with Wi-Fi & MDS (direct/indirect)		-	-	-	-
	AI Auto Comfort with Wi-Fi		●	●	●	●
	Auto Mode (without Wi-Fi)		-	-	-	-
	Fast Cooling		●	●	●	●
	Good Sleep		●	●	●	●
	Eco		●	●	●	●
	Dehumidification		●	●	●	●
	Fan		●	●	●	●
Quiet		●	●	●	●	
Other Functions	Samsung SmartThings		●	●	●	●
	MDS (Motion Detect Sensor)		●	●	●	●
	Indoor Temperature Display		●	●	●	●
	Display On/Off	88 Display	●	●	●	●
	Beep On/Off		●	●	●	●
	Auto Changeover		●	●	●	●
	Auto Restart		●	●	●	●

Controls and Accessories



Wireless Remote Controller	Advanced Wired Controller ³	Simple Type Controller ³	Touch Controller ³
	MWR-WG01JN MWR-WG01KN	MWR-SH00N	MWR-SH11N

³ MIM-A00N Interface is required for the connection to wired remote controllers.